

# FEND® TOOL ATTACHMENT O RING

Model No.: FE-5011

## Specifications

- Material: Steel wire rope + PU
- Color: Orange
- Tools O-ring
- Diameter: 1.5mm
- Strength: 2lbs
- Girth length: 155mm
- Standards: ANSI/ISEA 121:2018

## Tool Tether Use & Inspection Requirements Intended Use

### ⚠ WARNING — Use Only as Directed

Tool tethers are designed exclusively for hand tools that:

- Weigh no more than the product's specified weight rating
- Include manufacturer approved attachment features, such as:
  - Attachment points
  - Integrated rings
  - Purpose built holes or connection interfaces

Only tools with these features may be safely secured using the appropriate tether end type

## User Competency Requirements

### TRAINED PERSONNEL ONLY

This product must be used only by individuals trained & competent in:

- Working with hand tools at height
- Operating near moving machinery
- Understanding dropped object prevention systems

## Pre Use Inspection Requirements

### INSPECT BEFORE EACH USE

Before every use, the user must perform a complete inspection to verify that the tether is in safe working condition

### Hardware Inspection

Check all hardware for:

- Abrasion • Deformation • Sharp edges • Cuts or surface damage

### Webbing / Material Inspection

Inspect all textile components for:

- Tears, cuts, fraying, or abrasion
- Discoloration or burns
- Holes, mold, or contamination
- Unsplicing or loose, pulled, or broken stitches
- Any other signs of wear or deterioration

### Coil Style Tether Inspection

For coil style products, check for:

- Cracks or slits • Stress risers
- Loss of retraction memory
- Any deformation of the coil profile

### Prohibited Use

#### NOT FOR WRIST ATTACHMENT

- Tool tethers are not designed or approved for use on the wrist
- Do not modify, adapt, or repurpose the tether for wrist mounted applications

### Removal From Service

DO NOT USE the tether if:

- Any condition listed above is present
- The tether is damaged
- The tether does not function correctly

Immediately **quarantine** the product and remove it from service

### Approved Anchor Points

#### ATTACH ONLY TO APPROVED ANCHORS

Tool tethers must be connected only to belts, harnesses, or anchors that include:

- Manufacturer intended attachment points
  - Rated and approved connection specifications
- Improvised or non rated anchor points are strictly prohibited

### Industries

-  Oil & Gas
-  Warehousing, Logistics & Distribution
-  Construction
-  Utilities & Facility Maintenance



*\*Picture for illustration purposes only*



Scan for website



## CONTACT DETAILS:

### Safety Plus World

(A division of Raja General Trading Company W.L.L.)

P.O. Box:4121, Safat 13042, Kuwait

sc@safetyplusworld.com | www.safetyplusworld.com

Call Us:

 +965 6695 5684

